



NOW AVAILABLE

Allweather Wood Exterior Class A Fire Retardant Treated Redwood Siding

Enhance your building projects with our 1x6 & 1x8 Redwood BEE Siding Profiles, treated with a Clear Exterior Class A Fire Retardant Treatment by Hoover.

This treatment ensures that your siding not only retains the natural beauty of redwood but also offers enhanced safety and fire protection. Designed for exterior applications, our fire-retardant-treated redwood meets the highest standards for durability and performance, especially in wildfire-prone areas

For availability, pricing, or to place an order, contact your Allweather Wood Sales Representative. General Inquires call 800-621-0991

CODE REFERENCES

Surface Burning Test
ASTM E84 / UL 723

Extended Surface Burning Test
ASTM E2768

Accelerated Weathering Test
ASTM D2898

California Building Code Chapter 7A
WUI and IWUIC Compliant

Kiln Dried After Treatment (KDAT)
IBC 2303.2.8

**California Fire Marshal Building
Materials Listing**
(2520-1701:0100) & (2580-1701:0101)

Pressure Process
IBC 2303.2.1



PASSES TOUGHEST FIRE TEST

With UL 723 and ASTM E84 compliance, maintaining flame spread indices below 25



CERTIFIED FOR USE IN CALIFORNIA

Compliant with Building Code Chapter 7A and WUI & IWUIC codes, making it perfect for wildfire-prone areas



KILN-DRIED AFTER TREATMENT (KDAT)

To minimize warping and cracking while improving dimensional stability



DURABILITY OUTDOORS

No increase in the flame spread classification when subjected to ASTM D2898 (Standard Rain Test)